

SIT-1002 DATA SHEET



Cellular and Wireless

GSM/EDGE (850, 900, 1800, 1900 MHz)
802.11b/g/n WiFi

Brand: SHIPIT.TO

Model: SIT-1002

FCCID: 2AVD4SIT1002

Size and Weight¹

Size:
66mm x 35mm x 14mm
2.6in x 1.38in x 0.55in

Weight:
40 grams (1.4 oz)



Power and Battery²

Built-in rechargeable 1000mAh lithium-ion battery

Stand-by:
Up to 90 days
Average current < 100µA

Charging:
Charging via the provided charging cable or shipit.to charging case
Battery charge time ~ 4 hours

Environmental Requirements

Operating ambient temperature:
-10° to 55° C (14° to 131° F)

Nonoperating temperature:
-20° to 85° C (-4° to 185° F)

Relative humidity:
5% to 95% Non-condensing

Operating altitude: 3000 m (10,000 feet)

Rated IPX7³ (maximum depth of 1 meter up to 30 minutes) under IEC standard 60529

Temperature Sensor

Range: -40° to 87.5° C (-40° to 189.5° F)

Accuracy: ±0.5° C



¹ Size and weight may vary by configuration and manufacturing process.

² All battery claims depend on network configuration and many other factors; actual results will vary. Battery has limited recharge cycles. Battery life and charge cycles vary by use and settings.

³ Splash, water, and dust resistance are not permanent conditions and resistance might decrease as a result of normal wear. Do not attempt to charge a wet tracker.